

FIREBULL®

Class A Wetting Agent



FIREBULL® is manufactured by EnforcerOne, LLC.
Contact EnforcerOne for more details at
678-788-8413 or info@enforcerone.com
www.enforcerone.com

PRODUCT INFO:

Environmentally formulated FIREBULL Class A Foam is the newest generation in nonfluorinated foam. FIREBULL Class A Foam contains ZERO hazardous materials in the formulation; it will not clog, gum, or corrode foam systems and equipment. This environmentally formulated concentrate implements a dramatically changed chemistry compared to most foams. This chemistry enables FIREBULL Class A Foam to be used in all types of foam portioning systems, compressed air foam systems (CAFS), in-line eductors, and standard foam equipment.

APPLICATIONS

Grass fires and Initial Structural
Knockdown: 0.10% - 0.25%
Tire Fires, Landfill Fires, Coal
Fires and Wildland Fires:
0.25% - 0.50%
Car/Vehicle Fires and Overhaul:
0.50% - 1.0%

APPLICATION NOTES

Recommended to set foam
system defaults between 0.25%
and no more than 0.50%
Compressed Air Foam Systems
(CAFS) should be calibrated
using a foaming solution under
50 cps for accurate calibration

FLUSHING INSTRUCTIONS

It is recommended to flush all
Class A foam tanks if possible. If
not, use as much of previous Class
A foam, then add FIREBULL
concentrate. Mixing with most
Class A foams will not cause harm
to systems.

SHELF LIFE

FIREBULL Class A foam has an
unlimited shelf-life.

COMPATIBILITY

Compatible with other brands of
foam as finished foam.
Compatible with other FIREBULL
products as a concentrate.

PHYSICAL PROPERTIES

Appearance: Natural Amber
PH: 7.5-8.5
Viscosity: 2.382 cps
Min. Storage Temp: 35°F (2°C)
Max. Storage Temp: 120°F (-49°C)
Effect of Freeze/Thaw: None



Associated Products



**FIREBULL
FLUORINE FREE FOAM**



**FIREBULL
TRAINING FOAM**



ENFORCER 30 CAFS



ENFORCER 10 CAFS